


POLY-CLASSIC® *Craftsman Series Column Wraps*

NON-TAPERED COLUMNS

are available plain, fluted or with three paneled options: standard raised panel, "square corner" raised panel, and recessed panel. (Since all tooling used for routing the panels is done with round bits, there will always be some radius in the corners. The "square corner" style uses the smallest bit possible to minimize that radius - about 1/8".) Double panel configurations are available upon request, similar to the panels on Turncraft's Poly-Classic FRP square column shafts, or with custom spacing.


PLAN TYPES

Craftsman Series are available in the following plan types. Please specify when you order. (Customer may specify actual returns, wall thicknesses, etc.) Plan O & N are available only as non-tapered.




PRECISION MITER JOINTS

Vertical edges of Craftsman shafts (tapered, non-tapered, pedestal and newel post styles) all incorporate the E-Z Lock miter joint for consistently straight miters.



Panel Styles



Nominal width	Shaft dimensions		Panel and flute spacing †		Panels †		Flutes	
	Net bottom width	Inside bottom width	From bottom of shaft ‡	From top of shaft	From side of shaft	Width of routed channel	Number of flutes	Flute width
	(B)	(C)	(D)	(E)	(G)	(F)		
6"	5 5/8"	4 3/8"	16 3/4"	8 1/2"	1 1/4"	3/4"	20	1/2"
8"	7 5/8"	6 3/8"	16 3/4"	8 1/2"	1 1/2"	1 1/4"	20	3/4"
10"	9 5/8"	8 3/8"	16 3/4"	8 1/2"	1 1/2"	1 1/4"	20	1"
12"	11 5/8"	10 3/8"	16 3/4"	8 1/2"	1 1/2"	1 1/4"	20	1 1/4"
14"	13 5/8"	12 3/8"	16 3/4"	9"	2"	1 1/4"	24	1 1/4"
16"	15 5/8"	14 3/8"	16 3/4"	9 1/4"	2 1/4"	1 1/4"	28	1 1/4"
18"	17 5/8"	16 3/8"	16 3/4"	9 1/2"	2 1/2"	1 1/4"	32	1 1/4"
20"	19 5/8"	18 3/8"	16 3/4"	9 3/4"	2 3/4"	1 1/4"	36	1 1/4"
22"	21 5/8"	20 3/8"	16 3/4"	10"	3"	1 1/4"	40	1 1/4"
24"	23 5/8"	22 3/8"	16 3/4"	10 1/4"	3 1/4"	1 1/4"	44	1 1/4"

† Dimensions except width also apply to recessed panel shafts.

‡ Dimension shown is for standard shafts. On custom height columns the panels/flutes start 4" from the top of the base selected, and dimension (G) from the cap (or optional neck moulding).

Nominal column width	Standard sizes (A)					8'	10'	12'	14'	16'	18'	20'	22'	24'
	4'	5'	6'	8'	10'									
14"	✓	✓	✓	✓	✓									
16"	✓	✓	✓	✓	✓									
18"	✓	✓	✓	✓	✓									
20"	✓	✓	✓	✓	✓									
22"	✓	✓	✓	✓	✓									
24"	✓	✓	✓	✓	✓									

Custom widths and heights may be requested in any size up to 24' tall and 48" wide. Cap and base trim and platforms will be adjusted as needed for the revised shaft width.

