


Non-Tapered Round Shafts Available Heights and Load Capacities								
Column Bottom Diameter ‡	8'	10'	11'	12'	14'	15'	Concentric Load *	Eccentric Load *
8"	√	√					10,000 lb.	8,240 lb.
10"	√	√					14,000 lb.	11,520 lb.
12"	√	√		√			18,000 lb.	11,520 lb.
14"	√	√		√	√		20,000 lb.	18,120 lb.
16"	√	√					20,000 lb.	13,200 lb.
18"	√	√	√				20,000 lb.	9,040 lb.
20"	√	√	√				20,000 lb.	18,960 lb.
24"	√	√		√	√	√	20,000 lb.	13,200 lb.



All Poly-Classic® FRP Columns are available with custom fluting.
 √ Available unfluted.

FLAME GUARD


Poly-Classic® FRP Columns were the first fiberglass-reinforced polymer columns to achieve the distinction of passing an industry test (ASTME, 84-01) that measures the flame spread and smoke development of building components in a fire.

Turncraft Poly-Classic® FRP Columns with Flame Guard set a new industry standard:		
Industry Standard for FRP Columns	Flame Spread Index (FSI)	Smoke Developed Index (SDI)
Turncraft Poly-Classic® Columns	15*	335**

*Achieving Class I Flame-Spread classification under 1997 uniform fire code. **Well below the allowable SDI index of 450.

PLAN TYPES

Poly-Classic® FRP Columns are available in the plan types below. Please specify when you order. (Fractional components shown are typical. Customer may specify actual returns, wall thicknesses, etc.)




POLY-CLASSIC® SHAFTS FOR ROUND NON-TAPERED FRP COLUMNS

Standard FRP column shafts are the same height as the listed size. Tuscan caps and bases and Attic bases go around the shaft, and do not affect the overall height. Ornamental capitals are not typically available for non-tapered round shafts.

Column nominal diameter	Shaft height (A)	Shaft diameters *		Space available inside shaft		Flute width (24 each)	Concentric Load	Eccentric Load
		Outside diameter (B)	Inside diameter (C)	For round post	For square post			
8"	8'	7 5/8"	6 3/4"	6 3/8"	4 1/2"	1 1/16"	10,000 lb.	6,600 lb.
	10'							
10"	8'	9 1/16"	8 3/8"	8"	5 5/8"	7/8"	14,000 lb.	10,720 lb.
	10'							
12"	8'	11 5/8"	10 3/4"	10 3/8"	7 5/16"	1"	18,000 lb.	13,200 lb.
	10'							
14"	8'	13 1/2"	11 1/2"	11 1/8"	7 7/8"	1 5/16"	20,000 lb.	11,520 lb.
	10'							
	12'							
16"	8'	15 1/16"	13 1/2"	13"	9 3/16"	1 1/2"	20,000 lb.	13,200 lb.
	10'							
18"	8'	17 3/8"	15"	14 1/2"	10 1/4"	1 11/16"	20,000 lb.	9,040 lb.
	10'							
20"	8'	19 3/8"	18"	16 1/2"	11 5/8"	1 7/8"	20,000 lb.	18,960 lb.
	10'							
24"	8'	23 3/8"	21 1/4" (top ID)	19 1/2"	13 3/4"	2 5/16"	20,000 lb.	13,200 lb.
	10'							
	12'							
	14'							

* Diameters may vary ± 1/8".



The "Space Available Inside Shaft" measurements are calculated at the top inside diameter (with ± 3/8" tolerance) when using Tuscan or Roman Doric caps. Fluted columns may have reduced tolerances.

